

RLX 1000 Series: SIL3 Safety Relay Modules



RLX 1010

RLX 1020

Product Type:

SIL3 Safety Relay Module

SIL3 Safety Relay Module with diagnostics

Function:

Safety-related switching

Safety-related switching with line & load diagnostics

Channel(s):

1 Channel

1 Channel

Power:

24 Vdc (20 - 30 Vdc)

24 Vdc (20 - 30 Vdc)

Input:

24 Vdc

24 Vdc

Safety Outputs:

1×SPST(NE) + 1×SPST(ND)

1×DPST(NE) + 1×SPST(ND)

Contact Rate:

3 A @ 250 Vac / 125 Vdc (resistive)

3 A @ 250 Vac / 125 Vdc (resistive)

LEDs:

Relay status (Yellow)

Power (Green), Status (Yellow), Fault (Red)

Dimension:

22.5 × 99 × 114.5 mm

22.5 × 99 × 114.5 mm

Weight:

≈ 110 g

≈ 150 g

Mounting:

35 mm DIN rail

35 mm DIN rail

Ingress Protection:

IP20

IP20

Operating Temperature:

−20 ° to +60 °C

−20 ° to +60 °C

Fire and Gas
Detection System



SGIA

SIMIN GAMAN ARIA GROUPS

www.sga-safety.ir